

SPECS

SUPREME 7000 is a synthetic blend motor oil. It is scientifically blended from 100% pure paraffin base oils PLUS the finest quality synthetic base stocks. It withstands a higher heat range than conventional oils (*up to 250° more*). AND it starts easier in cold weather (*down to -25°F*).

SUPREME 7000 is also blended with two proven friction modifiers, soluble Moly and Penetro®, to reduce engine wear, increase engine life, and improve fuel economy.

EXCEEDS API SEQUENCE TEST
CI-4 PLUS/CH-4/SL, CI-4 PLUS, (SAE 15W-40 ONLY)
EXCEEDS CUMMINS, CES 20076 & 20078 CAT ECF-1,
DETROIT & MACK EO-N-03 PREMIUM PLUS, VOLVO
SPECS. EXCEEDS MIL-PRF-2104G, ACEA E5/B3/A3.

IN ADDITION

EXCEEDS FORD, GM, CHRYSLER, ALL FOREIGN
MANUFACTURERS SPECS FOR PRE-1994 GASOLINE
ENGINES. (AFTER 1994, 5W-30 OR 10W-30 IS
REQUIRED FOR WARRANTY PURPOSES.)

SUPREME 7000 is a universal oil for use in both gas and diesel engines. It substantially exceeds the American Petroleum Institute CI-4, CI-4 PLUS and CH-4 classification for diesel engines, as well as the "SL" classification for gas engines.

It exceeds all major manufacturers' specifications, including Detroit Diesel's specs. It is formulated to exceed the 1998, 1999 & 2002 emission standards for diesel engines. **Also available in 5W-30 and 10W-30.**

Specify: 701 SUPREME 7000 SAE 5W-30 SM ENERGY CONSERVING, ILSAC GF-4; 703 SUPREME 7000 SAE 10W-30 SM, ENERGY CONSERVING, ILSAC GF-4

